

CLEANING AND MAINTENANCE

With regular cleaning it is possible to preserve the quality, durability and extend the lifetime of resilient floors and wall cladding.

Cleaning: Remove loose dirt from the floor with dry cleaning methods (vacuuming, sweeping). Add 50 ml Bona Clean R50 to 10 litres of clean, cold water for normal cleaning. For heavily soiled floors, add up to 250 ml Bona Clean R50 to 10 litres of cold water. If using a concentration, greater than 150 ml in 10 litres water, you must neutralize the surface afterwards by cleaning with clean water. For large areas, Bona Clean R50 can also be used with power scrubbers, such as the Bona Power Scrubber.

Maintenance: For routine cleaning, dilute Bona Clean R60, 50 ml to 10 litres cold water and wipe the floor with the solution then let it dry. Where there is heavy contamination, dilute 250 ml to 10 litres water. This will clean and protect the surface at the same time.



Clean R50 Clean R60

DEEP CLEANING

Over time and heavy wear, stubborn stains and residue build up, resulting in tired, dull surfaces. Deep Cleaning is an alternative that restores the freshness without the need for renovation.

Deep Cleaning: Vacuum or dust mop the application area. Use Bona Remove R diluted with water. Add water according to the level of contamination (dilution 1:1-1:5) and apply with a mop. Allow the solution to penetrate. Scrub the surface by using the Bona FlexiSand 1.9 with the standard mounting plate and a red or green pad. Remove the dissolved maintenance residues by using the Bona PowerScrubber with red brushes and then neutralize the floor with clear water with white brushes.

After cleaning and drying, we recommend using Bona Shield as a protective layer.



Power Remove R Remove R

PROTECTING THE SURFACE

A new protective layer will restore the original lustre and prolong the life of the floor. The Bona process is a safe, quick and easy protective treatment that will restore the surface and bring the floor back to life.

Cleaning: Vacuum or dust mop the application area. Perform the regular daily cleaning routine using a diluted solution of Bona Clean R50. Where there is heavy soiling, use diluted Bona Remove R. (Note that any residual dirt will remain trapped in the coating.) Add water according to the level of contamination (dilution 1:1-1:5) and apply with a mop. Allow the solution to penetrate. Then scrub the surface using the Bona FlexiSand 1.9 with the standard mounting plate and a red pad, or with the Bona Power Scrubber with red brushes. Remove the dissolved maintenance residues by using the Bona PowerScrubber and then neutralize the floor with clear water and white brushes.

Protecting: When the surface is dry, shake the Bona Shield R container thoroughly before use, then apply a thin, consistent coat (1-2 layers) using a Bona Applicator Pad.

Allow to dry for 1-2 hours. Bona Shield R is available in matt and gloss versions.



Remove R Shield R

RECOATING - RENOVATION

Recoating provides a tough, protective layer to the floor's surface and extends its life. It also removes scuff marks and superficial scratches, and restores the overall appearance and slip resistance.

Cleaning: Vacuum or dust mop the application area. Make any local repairs. Mix the Bona Power Remove R with water according to the level of contamination (dilution 1:1-1:5) and apply with a mop. Allow the solution to penetrate the surface. Scrub the surface by using the Bona FlexiSand 1.9, attach the abrasives to a Bona Quattro Disc. Superficially abrade the surface using Bona Diamond Abrasives. Clean any dirt from the surface using the Bona PowerScrubber, then neutralize the floor with clear water. Let it dry.

Recoating: Mix Bona Pure or Bona Pure Colour with the accompanying hardener in a bucket. Apply using a Bona Polyester Roller. Let it dry for a minimum of 24 hours.



Power Remove R Pure Pure Colour



● CLEANING AND MAINTENANCE



● PROTECTING THE SURFACE



● DEEP CLEANING



● RECOATING - RENOVATION



LVT IMPERIO	●	●	●	●
LVT Thermofix	●	●	●	●
DOMO	●	●	●	●
Novoflor Standard	●	●	●	●
Novoflor Extra	●	●	●	●
DUAL	●	●	●	●
PRAKTIK	●	●	●	●
Floating vinyl WELL-click	●	●	●	●
ELEKTROSTATIK	●	●	●	●
DYNAMIK	●	●	●	●
Novoflor Extra Statik SD, DUAL SD, GARIS	●	●	●	●
Novoflor Extra AMOS	●	●	●	●
Floating vinyl FatraClick	●	●	●	●
Floating vinyl RS-click	●	●	●	●
MODUL	●	●	●	●

● Protection of the surface without using a lot of water – clean only with a mop.

Clean and fresh floors

With regular cleaning it is possible to preserve the quality, durability and extend the lifetime of resilient floors, and at the same time maintain a clean, healthy indoor environment. The Bona Care Program is a unique, effective method that delivers quick, efficient cleaning with a guaranteed, fantastic result. Bona Clean R60 provides gentle cleaning care with a shiny protective sheen, bringing out the best in a wide range of resilient floor coverings. The highly concentrated, alkaline formula of Bona Clean R50 takes the hard work out of stubborn stains and is suitable for both manual and machine application. All Bona products are formulated to provide outstanding performance without the use of harmful chemicals, making them ideal for everyday use, in every environment.